



MEMBRÁNOVÉ SIRÉNY SAMOSTATNÉ

Série KLH/KDH

710100004

KLH siréna s trychtýřem 12Vss

- Membránová siréna
- 92 dB
- Verze s trychtýřem i bez trychtýře



POPIS PRODUKTU

Tradiční jednoduchá membránová siréna pro vnitřní použití.

SPECIFIKACE

Barva těla	Šedá RAL 7035
Druh montáže	Vertikální
Frekvence max.	50 Hz
Frekvence min.	50 Hz
Hladina zvuku max.	92 dB
Hladina zvuku min.	92 dB
Hmotnost	180 g
Jmenovitý proud max.	0,055 A
Jmenovitý proud min.	0,055 A
Napájecí napětí	12 V
Napájecí napětí DC max.	13,2 V DC
Napájecí napětí DC min.	10,8 V DC
Počet tónů	1 ks
Provozní teplota max.	50 °C
Provozní teplota min.	-25 °C

Průřez vodičů	2,5 mm ²
Třída krytí	IP43, NEMA Type 2

The sound pressure decreases by 6 dB when doubling the distance; the following distance table is to be seen as indication, as also factors like tone type, wind speed, wind direction, humidity, weather conditions etc. do influence the sound pressure level.

Distance (m)	Sound pressure dB (A)																			
1	65	70	75	80	85	90	92	94	96	98	100	102	104	106	108	110	112	114	116	118
2	59	64	69	74	79	84	86	88	90	92	94	96	98	100	102	104	106	108	110	112
3	55	60	65	70	75	80	82	84	86	88	90	92	94	96	98	100	102	104	106	108
5	51	56	61	66	71	76	78	80	82	84	86	88	90	92	94	96	98	100	102	104
10	45	50	55	60	65	70	72	74	76	78	80	82	84	86	88	90	92	94	96	98
20	39	44	49	54	59	64	66	68	70	72	74	76	78	80	82	84	86	88	90	92
30	35	40	45	50	55	60	62	64	66	68	70	72	74	76	78	80	82	84	86	88
50	30	36	41	46	51	56	58	60	62	64	66	68	70	72	74	76	78	80	82	84
100																				
200																				
500																				

The sound pressure decreases by 6 dB when doubling the distance

