



## DISTRIBUČNÍ BLOK, JEDNOSTRANNÝ


Série ADAPTERS

6047 1/4-1/8-2

Distribuční blok G1/4 - 2x G1/8




- Tělo z hliníku
- Až 6 připojení



### POPIS PRODUKTU

## SPECIFIKACE

Balení	10 ks
Materiál těla	Hliník
Procesní připojení	G1/4
Provozní teplota max.	300 °C
Provozní teplota min.	-20 °C
Tlakový rozsah max.	100 bar
Tlakový rozsah min.	-0,99 bar
Tvar těla	I



	A	B	H	C	D	L1	L2	L	D
6047 1/4-1/8-2	1/4	1/8	2	18	24	30	17,5	95	4,5
6047 1/4-1/8-3	1/4	1/8	3	18	24	30	17,5	95	4,5
6047 1/4-1/8-4	1/4	1/8	4	18	24	30	17,5	125	4,5
6047 1/4-1/8-5	1/4	1/8	5	18	24	30	17,5	155	4,5
6047 1/4-1/8-6	1/4	1/8	6	18	24	30	17,5	185	4,5
6047 3/8-1/4-2	3/8	1/4	2	22	30	36	20,0	76	5,5
6047 3/8-1/4-3	3/8	1/4	3	22	30	36	20,0	112	5,5
6047 3/8-1/4-4	3/8	1/4	4	22	30	36	20,0	148	5,5
6047 3/8-1/4-5	3/8	1/4	5	22	30	36	20,0	184	5,5
6047 3/8-1/4-6	3/8	1/4	6	22	30	36	20,0	220	5,5
6047 1/2-3/8-2	1/2	3/8	2	26	35	40	25,0	90	5,5
6047 1/2-3/8-3	1/2	3/8	3	26	35	40	25,0	130	5,5
6047 1/2-3/8-4	1/2	3/8	4	26	35	40	25,0	170	5,5
6047 1/2-3/8-5	1/2	3/8	5	26	35	40	25,0	210	5,5
6047 1/2-3/8-6	1/2	3/8	6	26	35	40	25,0	250	5,5

