




2-4 PÓLOVÉ ROZVODOVÉ BLOKY

RPQ1025

4pólová svorkovnice - RPQ C-100

- 40 A až 160 A.
- Samozhášivá izolační konstrukce UL 94-V0
- Izolace mezi fázemi
- Mosazné vodiče



POPIS PRODUKTU

SPECIFIKACE

Connections	8
Fix. Hole space	55 mm
Height (H)	75 mm
Input A: diameter	8,5 mm
Input A: torque, max.	1,5
Input A: wire cross-section stranded, max.	35 mm ²
Input A: wire cross-section stranded, min.	6 mm ²
Input A: wire cross-section with wire-end ferrules, max.	25 mm ²
Input A: wire cross-section with wire-end ferrules, min.	6 mm ²
Length (L)	98 mm
Nominal insulation voltage	690 V
Nominální proud	100 A
Number of inputs A	1
Number of outputs A	5
Number of outputs B	2
Output A: diameter	5,5 mm
Output A: torque, max.	0,8

Output A: wire cross-section stranded with wire-end ferrules, max.	6 mm ²
Output A: wire cross-section stranded with wire-end ferrules, min.	1,5 mm ²
Output A: wire cross-section stranded, max.	6 mm ²
Output A: wire cross-section stranded, min.	1,5 mm ²
Output B: diameter	6 mm
Output B: torque, max.	1,5
Output B: wire cross-section stranded with wire-end ferrules, max.	10 mm ²
Output B: wire cross-section stranded with wire-end ferrules, min.	1,5 mm ²
Output B: wire cross-section stranded, max.	16
Output B: wire cross-section stranded, min.	1,5 mm ²
Screw type	Galvanized steel screws
Short-circuit current resistance ICW over 1s	4,2 kA
Short-circuit current resistance IPK (peak value)	24 kA
Třída krytí	IP20
Width (P)	49 mm

