



PNEUMATICKÉ VÁLCE G454

Série G454

G454A53K2000A00

Pneumatický válec Ø50, 2000 mm, PUR

- ISO 15552
- Ø32mm až 100mm
- Zdvih 5mm až 1 000mm
- Jedno nebo dvojčinné



POPIS PRODUKTU

SPECIFIKACE

Jádro a pevné jádro	POM
Materiál čela	Slitina
Materiál těla	Eloxovaný hliník
Matice pístnice	Nerez ocel
Pístnice	Nerez ocel 316L
Pracovní tlak max.	10 bar
Provozní teplota max.	70 °C
Provozní teplota min.	-20 °C
Průměr pístu	50 mm
Těsnění pístu	PUR
Těsnění tlumení	PUR
Vnitřní píst	POM
Zdvih	2000 mm

DIMENSIONS (mm), WEIGHT (kg)



Configurator : CAD Files



① Stroke
② Stroke x 2
* Width across flange


Q	A	OB	E	OE	OK	KV	L	M	OM	N	PL	DR	SW	TG	VA	VO	WN	Z	ZB	W	WPT
mm		mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
32	22	30	16	48	G1/8	M10x1.25	18	5	17	94	12	142	14	M8	10	32.5	10	30	130	148	0.0029
40	24	35	16	54	G1/8	M12x1.25	19	6	19	100	14	159	16	M8	13	38	11	30	135	160	0.0037
50	32	40	16	66	G1/4	M16x1.5	24	8	24	106	20	175	18.5	M8	17	46.5	11	37	143	180	0.0053
63	52	45	16	78	G3/8	M20x1.5	24	8	24	121	20	190	19	M8	17	56.5	11	37	158	195	0.0057
80	63	55	17	86	G1/2	M20x1.5	30	10	33	128	25	214	16.5	M10	22	72	11	46	174	220	0.0086
100	80	65	17	115	G1/2	M20x1.5	30	10	33	138	25	224	16.5	M10	22	72	11	46	174	220	0.0086

(1) Thread components G have standard thread according to ISO 16035.


(2) Cylinder weight at 0 mm stroke.

(3) Weight to be added per additional mm length.

DIMENSIONS (mm), WEIGHT (kg)



Configurator : CAD Files



① Stroke
② Stroke x 2
* Width across flange

Q	A	OB	E	OE	OK	KV	L	M	OM	N	PL	DR	SW	TG	VA	VO	WN	Z	ZB	W	WPT
mm		mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
32	22	30	16	48	G1/8	M10x1.25	18	5	17	94	12	142	14	M8	10	32.5	10	30	130	148	0.0029
40	24	35	16	54	G1/8	M12x1.25	19	6	19	100	14	159	16	M8	13	38	11	30	135	160	0.0037
50	32	40	16	66	G1/4	M16x1.5	24	8	24	106	20	175	18.5	M8	17	46.5	11	37	143	180	0.0053
63	52	45	16	78	G3/8	M20x1.5	24	8	24	121	20	190	19	M8	17	56.5	11	37	158	195	0.0057
80	63	55	17	86	G1/2	M20x1.5	30	10	33	128	25	214	16.5	M10	22	72	11	46	174	220	0.0086
100	80	65	17	115	G1/2	M20x1.5	30	10	33	138	25	224	16.5	M10	22	72	11	46	174	220	0.0086

(1) Thread components G have standard thread according to ISO 16035.

(2) Cylinder weight at 0 mm stroke.

(3) Weight to be added per additional mm length.