



## VAKUOVÉ EJEKTORY LEM+

Série LEM+

LEM60X20SVAC15PG1

Vakuový ejektor, 60 %, Ø2,0 mm, NC, s ochranným krytem, s odfukem, 1xM12

- vrtanie 2 až 2,5mm
- spotřeba max.260 NI/min
- Podtlak max. 275 NI/min




### POPIS PRODUKTU


## SPECIFIKACE

<b>Funkce 1</b>	Normálně zavřený
<b>Hmotnost</b>	410 g
<b>Materiál</b>	PA6.6
<b>Materiál těsnění</b>	NBR
<b>Montáž</b>	Samostatná montáž
<b>Napájecí napětí max.</b>	7 bar
<b>Napájecí napětí min.</b>	4,5 bar
<b>Napětí</b>	24 V DC
<b>Průtok vakua</b>	189 NI/min
<b>Sound level</b>	75 dBA
<b>Spotřeba vzduchu</b>	179 NI/min
<b>Teplota okolí do</b>	50 °C
<b>Třída krytí</b>	IP65
<b>Úroveň vakua</b>	60 %
<b>Vnitřní díly</b>	Hliník, Mosaz
<b>Vrtání</b>	2 mm

Version: one M12 connector



Version: two M12 connectors




**2- For Vacuum Pumps of Model S** (vacuum control NC valve, blow-off control NC valve)




**3- For Vacuum Pumps of Model V** (vacuum control NO valve, blow-off control NC valve)




Version: one M12 connector



Version: two M12 connectors



**2- For Vacuum Pumps of Model S** (vacuum control NC valve, blow-off control NC valve)



**3- For Vacuum Pumps of Model V** (vacuum control NO valve, blow-off control NC valve)

