Poptávka

VAKUOVÉ EJEKTORY LEM+

Série LEM+

LEM60X20SVAC15PG1
Vakuový ejektor, 60 %, Ø2,0 mm, NC, s ochranným krytem, s odfukem, 1xM12




- vŕtanie 2 až 2,5mm
- spotřeba max.260 Nl/min
- Podtlak max. 275 Nl/min

POPIS PRODUKTU


SPECIFIKACE

Funkce 1	Normálně zavřený
Hmotnost	410 g
Materiál	PA6.6
Materiál těsnění	NBR
Montáž	Samostatná montáž
Napájecí napětí max.	7 bar
Napájecí napětí min.	4,5 bar
Napětí	24 V DC
Průtok vakua	189 Nl/min
Sound level	75 dBA
Spotřeba vzduchu	179 Nl/min
Teplota okolí do	50 °C
Třída krytí	IP65
Úroveň vakua	60 %
Vnitřní díly	Hliník, Mosaz
Vrtání	2 mm

▪ Version: one M12 connector




▪ Version: two M12 connectors



2- For Vacuum Pumps of Model S (vacuum control **NC** valve, blow-off control **NC** valve)


- **C14**: 1 M12 4-pin connector
- **C15**: 1 M12 5-pin connector
- **C24**: 2 M12 4-pin connectors




** externally controlled blow-off or automatic blow-off function → economy of an automation outlet.*

3- For Vacuum Pumps of Model V (vacuum control **NO** valve, blow-off control **NC** valve)


- **C14**: 1 M12 4-pin connector
- **C15**: 1 M12 5-pin connector
- **C24**: 2 M12 4-pin connectors



▪ Version: one M12 connector




▪ Version: two M12 connectors



2- For Vacuum Pumps of Model S (vacuum control **NC** valve, blow-off control **NC** valve)

- **C14**: 1 M12 4-pin connector
- **C15**: 1 M12 5-pin connector
- **C24**: 2 M12 4-pin connectors



** externally controlled blow-off or automatic blow-off function → economy of an automation outlet.*

3- For Vacuum Pumps of Model V (vacuum control **NO** valve, blow-off control **NC** valve)

- **C14**: 1 M12 4-pin connector
- **C15**: 1 M12 5-pin connector
- **C24**: 2 M12 4-pin connectors

