



Poptávka



JÍMKY TW45

Série TW45

TW45F-3244334

Jímka 10x8x0,9mm G1/2 G1/2F L=82mm

- Materiál nerez
- Připojení G




POPIS PRODUKTU

SPECIFIKACE

Insertion length	82 mm
Inside diameter	8 mm
Materiál	Nerez ocel
Průměr	10 mm
Thickness	0,9 mm

Dimensions in mm

Model TW45-F													
Material	E	N	Ø d ₁	Ø d ₂	Ø F ₁	H ₁	H ₂	K ₁	S	S ₁	SW	U ₁ ± 82 mm	U ₁ ± 382 mm
Stainless steel 1.4571													
G1/2 B G1/2	7	26	12	19	15	14	2,5	3,5	27	0,15	0,33		
G1/2 B G1/2	9	26	14	19	15	14	2,5	3,5	27	0,15	0,36		
G1/2 B G1/2	11	26	14	19	15	14	1,5	2,5	27	0,12	0,28		
G1/2 B G1/2	6,2	26	8	19	15	14	0,9	1	27	0,12	0,18		
G1/2 B G1/2	8,2	26	10	19	15	14	0,9	1	27	0,12	0,18		
G1/2 B G1/2	10,2	26	12	19	15	14	0,9	1	27	0,12	0,19		
G1/2 B G1/2	7	32	12	19	15	16	2,5	3,5	32	0,24	0,42		
G1/2 B G1/2	9	32	14	19	15	16	2,5	3,5	32	0,24	0,45		
G1/2 B G1/2	11	32	14	19	15	16	1,5	2,5	32	0,22	0,37		
G1/2 B G1/2	6,2	32	8	19	15	16	0,9	1	32	0,21	0,27		
G1/2 B G1/2	8,2	32	10	19	15	16	0,9	1	32	0,21	0,27		
G1/2 B G1/2	10,2	32	12	19	15	16	0,9	1	32	0,21	0,28		
G1/2 B G1/2	7	32	12	22	17	16	2,5	3,5	32	0,20	0,38		
G1/2 B G1/2	9	32	14	22	17	16	2,5	3,5	32	0,20	0,41		
G1/2 B G1/2	11	32	14	22	17	16	1,5	2,5	32	0,18	0,33		
G1/2 B G1/2	6,2	32	8	22	17	16	0,9	1	32	0,17	0,23		
G1/2 B G1/2	8,2	32	10	22	17	16	0,9	1	32	0,17	0,23		
G1/2 B G1/2	10,2	32	12	22	17	16	0,9	1	32	0,17	0,24		
G1/2 B G1/2	6,2	32	10	19	15	14	0,75	0,75	27	0,11	0,18		
G1/2 B G1/2	8,5	32	10	19	15	14	0,75	0,75	27	0,11	0,18		
G1/2 B G1/2	8,5	32	10	19	15	14	0,75	0,75	32	0,23	0,29		




Model TW45-G													
Material	Dimensions in mm									Weight in kg	U ₁ = 72 mm	U ₁ = 410 mm	
	E	N	Ø d ₁	Ø d ₂	Ø F ₁	K ₁	K ₂	S	S ₁				
Stainless steel 1.4571													
G1/2 B G1/2	7	26	12	14	12	2,5	3,5	27	0,14	0,34			
G1/2 B G1/2	9	26	14	14	12	2,5	3,5	27	0,14	0,37			
G1/2 B G1/2	11	26	14	14	12	1,5	2,5	27	0,12	0,30			
G1/2 B G1/2	6,2	26	8	14	12	0,9	1	27	0,13	0,20			
G1/2 B G1/2	8,2	26	10	14	12	0,9	1	27	0,13	0,20			
G1/2 B G1/2	10,2	26	12	14	12	0,9	1	27	0,13	0,20			
G1/2 B G1/2	7	32	12	16	14	2,5	3,5	32	0,22	0,43			
G1/2 B G1/2	9	32	14	16	14	2,5	3,5	32	0,22	0,46			
G1/2 B G1/2	11	32	14	16	14	1,5	2,5	32	0,20	0,38			
G1/2 B G1/2	6,2	32	8	16	14	0,9	1	32	0,21	0,28			
G1/2 B G1/2	8,2	32	10	16	14	0,9	1	32	0,21	0,28			
G1/2 B G1/2	10,2	32	12	16	14	0,9	1	32	0,20	0,27			

Dimensions in mm

Model TW45-F													
Material	E	N	Ø d ₁	Ø d ₂	Ø F ₁	H ₁	H ₂	K ₁	S	S ₁	SW	U ₁ ± 82 mm	U ₁ ± 382 mm
Stainless steel 1.4571													
G1/2 B G1/2	7	26	12	19	15	14	2,5	3,5	27	0,15	0,33		
G1/2 B G1/2	9	26	14	19	15	14	2,5	3,5	27	0,15	0,36		
G1/2 B G1/2	11	26	14	19	15	14	1,5	2,5	27	0,12	0,28		
G1/2 B G1/2	6,2	26	8	19	15	14	0,9	1	27	0,12	0,18		
G1/2 B G1/2	8,2	26	10	19	15	14	0,9	1	27	0,12	0,18		
G1/2 B G1/2	10,2	26	12	19	15	14	0,9	1	27	0,12	0,19		
G1/2 B G1/2	7	32	12	19	15	16	2,5	3,5	32	0,24	0,42		
G1/2 B G1/2	9	32	14	19	15	16	2,5	3,5	32	0,24	0,45		
G1/2 B G1/2	11	32	14	19	15	16	1,5	2,5	32	0,22	0,37		
G1/2 B G1/2	6,2	32	8	19	15	16	0,9	1	32	0,21	0,27		
G1/2 B G1/2	8,2	32	10	19	15	16	0,9	1	32	0,21	0,27		
G1/2 B G1/2	10,2	32	12	19	15	16	0,9	1	32	0,21	0,28		
G1/2 B G1/2	7	32	12	22	17	16	2,5	3,5	32	0,20	0,38		
G1/2 B G1/2	9	32	14	22	17	16	2,5	3,5	32	0,20	0,41		
G1/2 B G1/2	11	32	14	22	17	16	1,5	2,5	32	0,18	0,33		
G1/2 B G1/2	6,2	32	8	22	17	16	0,9	1	32	0,17	0,23		
G1/2 B G1/2	8,2	32	10	22	17	16	0,9	1	32	0,17	0,23		
G1/2 B G1/2	10,2	32	12	22	17	16	0,9	1	32	0,17	0,24		
G1/2 B G1/2	6,2	32	10	19	15	14	0,75	0,75	27	0,11	0,18		
G1/2 B G1/2	8,5	32	10	19	15	14	0,75	0,75	27	0,11	0,18		
G1/2 B G1/2	8,5	32	10	19	15	14	0,75	0,75	32	0,23	0,29		

Model TW45-G



Material	Dimensions in mm										Weight in kg	
	Ø	h	QD ₁	QD ₂	QF ₁	K ₁	K ₂	S	S ₁	Sw	U ₁ x 72 mm	U ₁ x 410 mm
Stainless steel 1.4371	G 1/8	G 1/8	7	26	12	14	12	2.5	3.5	27	0.14	0.34
	G 1/8	G 1/8	9	26	14	14	12	2.5	3.5	27	0.14	0.37
G 1/8	G 1/8	11	26	14	14	12	1.5	2.5	27	0.12	0.30	
G 1/8	G 1/8	6.2	26	8	14	12	0.9	1	27	0.13	0.20	
G 1/8	G 1/8	8.2	26	10	14	12	0.9	1	27	0.13	0.20	
G 1/8	G 1/8	10.2	26	12	14	12	0.9	1	27	0.11	0.18	
G 1/8	G 1/8	7	32	12	16	14	2.5	3.5	32	0.22	0.43	
G 1/8	G 1/8	9	32	14	16	14	2.5	3.5	32	0.22	0.46	
G 1/8	G 1/8	11	32	14	16	14	1.5	2.5	32	0.20	0.39	
G 1/8	G 1/8	6.2	32	8	16	14	0.9	1	32	0.21	0.29	
G 1/8	G 1/8	8.2	32	10	16	14	0.9	1	32	0.21	0.28	
G 1/8	G 1/8	10.2	32	12	16	14	0.9	1	32	0.20	0.27	