



# TERMOČLÁNKY TC47-AB

Série TC47-AB

TC47-AB  
Termoclánek



- Teplota -40°C až 750°C
- K, J, K, T
- Tělo nerez



## POPIS PRODUKTU

## SPECIFIKACE

**Provozní teplota max.**

750 °C

**Provozní teplota min.**

-40 °C

<b>Ajustable bayonet</b>	<b>Lead wire</b>
■ Spring up to 200 mm or 8" of adjustability	■ Fibreglass / fibreglass
■ Armour full lead length of adjustability	■ PTFE / PTFE
■ 3/16"	■ 1/4"
■ 1/4"	■ 3/8"
■ 4 mm	■ 4 mm
■ 6 mm	■ 6 mm
■ 8 mm	■ 8 mm
■ 10 mm	■ 10 mm
■ Others on request	■ Others on request
<b>Junction</b>	<b>Ajustable bayonet</b>
■ Grounded (unisolated)	■ Spring up to 200 mm or 8" of adjustability
■ Ungrounded (isolated)	■ Armour full lead length of adjustability
<b>Lead wire covering</b>	<b>Lead wire</b>
■ None	■ Fibreglass / fibreglass
■ Stainless steel overbraid (no tracer)	■ PTFE / PTFE
■ Tin copper overbraid	■ Tin copper overbraid
■ Interlocking flexible armour	■ Others on request
<b>Termination at lead end</b>	<b>Lead wire covering</b>
■ Bare ends	■ None
■ Standard thermo plug 2-pin (male)	■ Stainless steel overbraid (no tracer)
■ Miniature thermo plug 2-pin (male)	■ Tin copper overbraid
■ Miniature plug with cable clamp (male)	■ Interlocking flexible armour
<b>Probe length</b>	<b>Termination at lead end</b>
■ Standard plug with cable clamp (male)	■ Bare ends
■ Miniature plug with cable clamp (male)	■ Standard thermo plug 2-pin (male)
<b>Bayonet cap id Ø</b>	■ Miniature thermo plug 2-pin (male)
<b>Fits bayonet adapter</b>	■ Standard plug with cable clamp (male)
■ Single slot 11.4 mm (7/16") 11 mm O.D.	■ Miniature plug with cable clamp (male)
■ Double slot 11.4 mm (7/16") 11 mm O.D.	■ Lemos plug size 15 (male)
■ Single slot 12.4 mm (9/16") 12 mm O.D.	■ Lemos plug size 25 (male)
■ Double slot 14.2 mm (9/16") 12 mm O.D.	■ Screw-in plug, Binder (male)
■ Double slot 15.2 mm (19/32") 15 mm O.D.	■ Others on request
■ Others on request	
<b>Probe length</b>	<b>Calibration type</b>
■ 500 mm	■ J ANSI MC96.1 red Ø white Ø
■ 1000 mm	■ K ANSI MC96.1 red Ø yellow Ø
■ 1500 mm	■ T ANSI MC96.1 red Ø blue Ø
■ 2000 mm	■ J IEC 584-3 white Ø black Ø
■ 2500 mm	■ K IEC 584-3 white Ø brown Ø
■ Others on request	■ T IEC 584-3 white Ø green Ø
<b>Lead length</b>	■ J DIN 43714 blue Ø red Ø
■ 500 mm	■ K DIN 43714 green Ø red Ø
■ 1000 mm	■ T DIN 43714 brown Ø red Ø
■ 1500 mm	■ Others on request
■ 2000 mm	
■ 2500 mm	
■ Others on request	
<b>Calibration type</b>	
■ J ANSI MC96.1 red Ø white Ø	
■ K ANSI MC96.1 red Ø yellow Ø	
■ T ANSI MC96.1 red Ø blue Ø	
■ J IEC 584-3 white Ø black Ø	
■ K IEC 584-3 white Ø brown Ø	
■ T IEC 584-3 white Ø green Ø	
■ J DIN 43714 blue Ø red Ø	
■ K DIN 43714 green Ø red Ø	
■ T DIN 43714 brown Ø red Ø	
■ Others on request	