



TERMOMETRY IFC

Série IFC

IFC-14349092

Termometr Ø60, 0-120°C, L=1m, slät 50x8mm



- Expanzní
- Teplota -40°C až 400°C
- Ø60, Ø80, Ø100 mm
- Kapilára






POPIS PRODUKTU

SPECIFIKACE

| | |
|--------------------------------------|--------------|
| Capillary length | 1000 mm |
| Insertion length | 50 mm |
| Materiál kontaktní části | Mosaz |
| Materiál průhledu | Inertní plyn |
| Materiál těla | Plast |
| Plug diameter | 8 mm |
| Provozní teplota max. | 120 °C |
| Provozní teplota min. | 0 °C |
| Průměr | 60 mm |
| Temperature resistance of cable from | -40 °C |
| Temperature resistance of cable to | 120 °C |
| Teplota okolí do | 70 °C |
| Teplota okolí od | -20 °C |
| Třída krytí | IP54 |


Standard version




Standard version
Plain stem (without thread), SF94
Copper alloy
Insertion length = variable
Stem diameter Dd = 6, 8, 8.5, 10 mm




Rotatable connection with loose threaded connection
SF91/SF15 M14 x 1.5, R 1/4, R 1/2, R 3/4
Copper alloy
Insertion length = variable
Stem diameter Dd = 6, 8, 8.5, 10 mm






NS 72 x 72



NS 96 x 96




Standard version




Standard version
Plain stem (without thread), SF94
Copper alloy
Insertion length = variable
Stem diameter Dd = 6, 8, 8.5, 10 mm



Rotatable connection with loose threaded connection
SF91/SF15 M14 x 1.5, R 1/4, R 1/2, R 3/4
Copper alloy
Insertion length = variable
Stem diameter Dd = 6, 8, 8.5, 10 mm



NS 72 x 72



NS 96 x 96

