



# TERMOČLÁNKY TC47-AB

Série TC47-AB



TC47-AB  
Termočlánek

- Teplota -40°C až 750°C
- K, J, K, T
- Tělo nerez



## POPIS PRODUKTU

## SPECIFIKACE

Provozní teplota max.	750 °C
Provozní teplota min.	-40 °C

**Adjustable bayonet**

- Spring up to 200 mm or 8" of adjustability
- Armour full lead length of adjustability

**Junction**

- Grounded (unisolated)
- Ungrounded (isolated)

**Tip diameter (Ø)**

- 3/16"
- 1/4"
- 3/8"
- 4 mm
- 6 mm
- 8 mm
- 10 mm
- Others on request

**Probe length**

- Standard
- Others on request

**Bayonet cap** | **Id Ø** | **Fits bayonet adapter**

- Single slot 11.4 mm (7/16") 11 mm O.D.
- Double slot 11.4 mm (7/16") 11 mm O.D.
- Double slot 12.2 mm (3/16") 12 mm O.D.
- Double slot 14.2 mm (9/16") 12 mm O.D.
- Double slot 15.2 mm (19/32") 15 mm O.D.
- Others on request

**Lead wire**

- Fibreglass / Fibreglass
- PTFE / PTFE
- PVC / PVC
- Kapton / Kapton
- Others on request

**Lead wire covering**

- None
- Stainless steel overbraid (no tracer)
- Stainless steel overbraid (with tracer)
- Tin copper overbraid
- Interlocking flexible armour

**Termination at lead end**

- Bare ends
- Standard thermo plug 2-pin (male)
- Miniature thermo plug 2-pin (male)
- Standard plug with cable clamp (male)
- Miniature plug with cable clamp (male)
- Lemoosa plug size 1S (male)
- Screw-in plug, Binder (male)
- Others on request

**Calibration type**

- J ANSI MC96.1 red Ø white Ø
- K ANSI MC96.1 red Ø yellow Ø
- T ANSI MC96.1 red Ø blue Ø
- J IEC 584-3 white Ø black Ø
- K IEC 584-3 white Ø green Ø
- T IEC 584-3 white Ø brown Ø
- J DIN 43714 blue Ø red Ø
- K DIN 43714 green Ø red Ø
- T DIN 43714 brown Ø red Ø
- Others on request

**Adjustable bayonet**

- Spring up to 200 mm or 8" of adjustability
- Armour full lead length of adjustability

**Junction**

- Grounded (unisolated)
- Ungrounded (isolated)

**Tip diameter (Ø)**

- 3/16"
- 1/4"
- 3/8"
- 4 mm
- 6 mm
- 8 mm
- 10 mm
- Others on request

**Probe length**

- Standard
- Others on request

**Bayonet cap** | **Id Ø** | **Fits bayonet adapter**

- Single slot 11.4 mm (7/16") 11 mm O.D.
- Double slot 11.4 mm (7/16") 11 mm O.D.
- Double slot 12.2 mm (3/16") 12 mm O.D.
- Double slot 14.2 mm (9/16") 12 mm O.D.
- Double slot 15.2 mm (19/32") 15 mm O.D.
- Others on request

**Lead wire**

- Fibreglass / Fibreglass
- PTFE / PTFE
- PVC / PVC
- Kapton / Kapton
- Others on request

**Lead wire covering**

- None
- Stainless steel overbraid (no tracer)
- Stainless steel overbraid (with tracer)
- Tin copper overbraid
- Interlocking flexible armour

**Termination at lead end**

- Bare ends
- Standard thermo plug 2-pin (male)
- Miniature thermo plug 2-pin (male)
- Standard plug with cable clamp (male)
- Miniature plug with cable clamp (male)
- Lemoosa plug size 1S (male)
- Screw-in plug, Binder (male)
- Others on request

**Calibration type**

- J ANSI MC96.1 red Ø white Ø
- K ANSI MC96.1 red Ø yellow Ø
- T ANSI MC96.1 red Ø blue Ø
- J IEC 584-3 white Ø black Ø
- K IEC 584-3 white Ø green Ø
- T IEC 584-3 white Ø brown Ø
- J DIN 43714 blue Ø red Ø
- K DIN 43714 green Ø red Ø
- T DIN 43714 brown Ø red Ø
- Others on request