



TERMOČLÁNKY TC47-MT

Série TC47-MT

TC47-MT Termočlánek

- Teplota -40°C až 750°C
- K, J, K, T
- Tělo nerez



POPIS PRODUKTU

SPECIFIKACE

Provozní teplota max.	750 °C
Provozní teplota min.	-40 °C

Manifold block <ul style="list-style-type: none"> Stainless steel Others on request 	Lead wire covering <ul style="list-style-type: none"> None Stainless steel overbraid (no tracer) Stainless steel overbraid (with tracer) Tin copper overbraid Interlocking flexible armour 	Manifold block <ul style="list-style-type: none"> Stainless steel Others on request 	Lead wire covering <ul style="list-style-type: none"> None Stainless steel overbraid (no tracer) Stainless steel overbraid (with tracer) Tin copper overbraid Interlocking flexible armour
Junction <ul style="list-style-type: none"> Grounded (unisolated) Ungrounded (isolated) 	Termination at lead end <ul style="list-style-type: none"> Bare ends Standard thermo plug 2-pin (male) Miniature thermo plug 2-pin (male) 	Junction <ul style="list-style-type: none"> Grounded (unisolated) Ungrounded (isolated) 	Termination at lead end <ul style="list-style-type: none"> Bare ends Standard thermo plug 2-pin (male) Miniature thermo plug 2-pin (male)
Tip diameter (Ø) <ul style="list-style-type: none"> 4 mm Others on request 	Standard plug with cable clamp (male) <ul style="list-style-type: none"> Standard plug with cable clamp (male) Miniature plug with cable clamp (male) 	Tip diameter (Ø) <ul style="list-style-type: none"> 4 mm Others on request 	Standard plug with cable clamp (male) <ul style="list-style-type: none"> Standard plug with cable clamp (male) Miniature plug with cable clamp (male)
Tip length <ul style="list-style-type: none"> 12 mm 20 mm 25 mm Others on request 	Lemosa plug size 1S (male) <ul style="list-style-type: none"> Lemosa plug size 1S (male) Lemosa plug size 2S (male) 	Tip length <ul style="list-style-type: none"> 12 mm 20 mm 25 mm Others on request 	Lemosa plug size 1S (male) <ul style="list-style-type: none"> Lemosa plug size 1S (male) Lemosa plug size 2S (male)
Lead length <ul style="list-style-type: none"> 500 mm 1000 mm 1500 mm 2000 mm 2500 mm Others on request 	Screw-in plug, Binder (male) <ul style="list-style-type: none"> Screw-in plug, Binder (male) Others on request 	Lead length <ul style="list-style-type: none"> 500 mm 1000 mm 1500 mm 2000 mm 2500 mm Others on request 	Screw-in plug, Binder (male) <ul style="list-style-type: none"> Screw-in plug, Binder (male) Others on request
Lead wire <ul style="list-style-type: none"> Fiberglass / Fiberglass PTFE / PTFE PVC / PVC Kapton / Kapton Others on request 	Calibration type <ul style="list-style-type: none"> J ANSI MC96.1 red Ø white Ø K ANSI MC96.1 red Ø yellow Ø T ANSI MC96.1 red Ø blue Ø J IEC 584-3 white Ø black Ø K IEC 584-3 white Ø green Ø T IEC 584-3 white Ø brown Ø J DIN 43774 blue Ø red Ø K DIN 43774 green Ø red Ø T DIN 43774 brown Ø red Ø Others on request 	Lead wire <ul style="list-style-type: none"> Fiberglass / Fiberglass PTFE / PTFE PVC / PVC Kapton / Kapton Others on request 	Calibration type <ul style="list-style-type: none"> J ANSI MC96.1 red Ø white Ø K ANSI MC96.1 red Ø yellow Ø T ANSI MC96.1 red Ø blue Ø J IEC 584-3 white Ø black Ø K IEC 584-3 white Ø green Ø T IEC 584-3 white Ø brown Ø J DIN 43774 blue Ø red Ø K DIN 43774 green Ø red Ø T DIN 43774 brown Ø red Ø Others on request