



Poptávka

JÍMKY TW45

Série TW45

TW45F-3278001

Jímka 12x6x2,5mm G1/2 G1/2F L=382mm

- Materiál nerez
- Připojení G



POPIS PRODUKTU

SPECIFIKACE

Insertion length 382 mm


Inside diameter 6 mm

Materiál Nerez ocel

Průměr 12 mm

Thickness 2,5 mm


Dimensions in mm



Legend:
E Process connection
N Length of male thread
H₁ Length of female thread
H₂ Length of male thread
K₁ Overall length
N Connection to thermometer
S Wall thickness
S₁ Tip thickness
SW Flange
U₁ Insertion length
Ø d₂ Bore size
Ø d₁ Diameter of the sealing collar
Ø F₁ Thermowell external diameter

Material	Dimensions in mm											Weight in kg	
	E	N	Ø d ₁	Ø F ₁	H ₁	H ₂	K ₁	S	S ₁	SW	U ₁ ± 0.2 mm	U ₁ ± 382 mm	U ₁ ± 382 mm
Stainless steel 1.4571	G 1/2	G 1/2	7	26	12	19	15	14	2.5	3.5	27	0.15	0.33
	G 1/2	G 1/2	9	26	14	19	15	14	2.5	3.5	27	0.15	0.36
	G 1/2	G 1/2	11	26	14	19	15	14	1.5	2.5	27	0.12	0.28
	G 1/2	G 1/2	8	26	8	19	15	14	0.9	1	27	0.12	0.18
	G 1/2	G 1/2	8.2	26	10	19	15	14	0.9	1	27	0.12	0.18
	G 1/2	G 1/2	10.2	26	12	19	15	14	0.9	1	27	0.12	0.19
	G 1/2	G 1/2	7	32	12	19	15	16	2.5	3.5	32	0.24	0.42
	G 1/2	G 1/2	9	32	14	19	15	16	2.5	3.5	32	0.24	0.45
	G 1/2	G 1/2	11	32	14	19	15	16	1.5	2.5	32	0.22	0.37
	G 1/2	G 1/2	8.2	32	8	19	15	16	0.9	1	32	0.21	0.27
Copper alloy	G 1/2	G 1/2	7	32	12	22	17	16	2.5	3.5	32	0.20	0.38
	G 1/2	G 1/2	9	32	14	22	17	16	2.5	3.5	32	0.20	0.41
	G 1/2	G 1/2	11	32	14	22	17	16	1.5	2.5	32	0.18	0.33
	G 1/2	G 1/2	8.2	32	8	22	17	16	0.9	1	32	0.17	0.23
	G 1/2	G 1/2	8.2	32	10	22	17	16	0.9	1	32	0.17	0.23
	G 1/2	G 1/2	10.2	32	12	22	17	16	0.9	1	32	0.17	0.24
	G 1/2	G 1/2	8.2	32	10	19	15	14	0.75	0.75	27	0.11	0.18
	G 1/2	G 1/2	8.5	32	10	19	15	16	0.75	0.75	32	0.23	0.29
	G 1/2	G 1/2	8.5	32	10	19	15	16	0.75	0.75	32	0.23	0.29
	G 1/2	G 1/2	8.5	32	10	19	15	16	0.75	0.75	32	0.23	0.29

Model TW45-G



Legend:
E Process connection
N Length of male thread
K₁ Length of male thread for thermometer
K₂ Overall length
N Connection to thermometer
S Wall thickness
S₁ Tip thickness
SW Flange
U₁ Insertion length
Ø d₂ Bore size
Ø d₁ Diameter of the sealing collar
Ø F₁ Thermowell external diameter

Material	Dimensions in mm											Weight in kg	
	E	N	Ø d ₁	Ø F ₁	K ₁	K ₂	S	S ₁	SW	U ₁ ± 0.2 mm	U ₁ ± 410 mm	U ₁ ± 410 mm	U ₁ ± 410 mm
Stainless steel 1.4571	G 1/2	G 1/2	7	26	12	14	12	2.5	3.5	27	0.14	0.34	0.37
	G 1/2	G 1/2	9	26	14	14	12	2.5	3.5	27	0.14	0.37	0.37
	G 1/2	G 1/2	11	26	14	14	12	1.5	2.5	27	0.12	0.30	0.30
	G 1/2	G 1/2	8.2	26	10	14	12	0.9	1	27	0.13	0.20	0.20
	G 1/2	G 1/2	10.2	26	12	14	12	0.9	1	27	0.13	0.20	0.20
	G 1/2	G 1/2	7	32	12	16	14	2.5	3.5	32	0.22	0.43	0.46
	G 1/2	G 1/2	9	32	14	16	14	2.5	3.5	32	0.22	0.46	0.46
	G 1/2	G 1/2	11	32	14	16	14	1.5	2.5	32	0.20	0.38	0.38
	G 1/2	G 1/2	8.2	32	8	16	14	0.9	1	32	0.21	0.28	0.28
	G 1/2	G 1/2	10.2	32	10	16	14	0.9	1	32	0.21	0.28	0.28
Copper alloy	G 1/2	G 1/2	7	32	12	17	16	2.5	3.5	32	0.20	0.38	0.38
	G 1/2	G 1/2	9	32	14	17	16	2.5	3.5	32	0.20	0.41	0.41
	G 1/2	G 1/2	11	32	14	17	16	1.5	2.5	32	0.18	0.33	0.33
	G 1/2	G 1/2	8.2	32	8	17	16	0.9	1	32	0.17	0.23	0.23
	G 1/2	G 1/2	8.2	32	10	17	16	0.9	1	32	0.17	0.23	0.23
	G 1/2	G 1/2	10.2	32	12	17	16	0.9	1	32	0.17	0.24	0.24
	G 1/2	G 1/2	8.2	32	10	19	16	0.75	0.75	27	0.11	0.18	0.18
	G 1/2	G 1/2	8.5	32	10	19	16	0.75	0.75	32	0.23	0.29	0.29
	G 1/2	G 1/2	8.5	32	10	19	16	0.75	0.75	32	0.23	0.29	0.29
	G 1/2	G 1/2	8.5	32	10	19	16	0.75	0.75	32	0.23	0.29	0.29