



JÍMKY TW45

Série TW45

TW45F-3244334

Jímka 10x8x0,9mm G1/2 G1/2F L=82mm

- Materiál nerez
- Připojení G



POPIS PRODUKTU

SPECIFIKACE

Insertion length 82 mm

Inside diameter 8 mm

Materiál Nerez ocel

Průměr 10 mm

Thickness 0,9 mm

Dimensions in mm

Model TW45-F

Legend:

- E Process connection
- N Length to female thread
- G Length of female thread
- d1 Length of male thread
- D Overall length
- F1 Connection to thermometer
- H1 Wall thickness
- H2 Tip thickness
- K1 Tip thickness
- S Wall thickness
- S1 Tip thickness
- SW Flange
- U1 Insertion length
- U2 Bore size
- D1 Diameter of the sealing collar
- F1 Thermowell external diameter

Material	Dimensions in mm														Weight in kg	
	E	N	G	d1	D	F1	H1	H2	K1	S	S1	SW	U1 x 82 mm	U2 x 382 mm		
Stainless steel 1.4571	G 1/2	G 1/2	7	26	12	19	15	14	2,5	3,5	27	0,15	0,33			
	G 1/2	G 1/2	9	26	14	19	15	14	2,5	3,5	27	0,15	0,36			
	G 1/2	G 1/2	11	26	14	19	15	14	1,5	2,5	27	0,12	0,28			
	G 1/2	G 1/2	8	26	8	19	15	14	0,9	1	27	0,12	0,18			
	G 1/2	G 1/2	8,2	26	10	19	15	14	0,9	1	27	0,12	0,18			
	G 1/2	G 1/2	10,2	26	12	19	15	14	0,9	1	27	0,12	0,19			
	G 1/2	G 1/2	7	32	12	19	15	16	2,5	3,5	32	0,24	0,42			
	G 1/2	G 1/2	9	32	14	19	15	16	2,5	3,5	32	0,24	0,45			
	G 1/2	G 1/2	11	32	14	19	15	16	1,5	2,5	32	0,22	0,37			
	G 1/2	G 1/2	8,2	32	8	19	15	16	0,9	1	32	0,21	0,27			
	G 1/2	G 1/2	8,2	32	10	19	15	16	0,9	1	32	0,21	0,27			
	G 1/2	G 1/2	10,2	32	12	19	15	16	0,9	1	32	0,21	0,28			
Copper alloy	G 1/2	G 1/2	7	32	12	22	17	16	2,5	3,5	32	0,20	0,38			
	G 1/2	G 1/2	9	32	14	22	17	16	2,5	3,5	32	0,20	0,41			
	G 1/2	G 1/2	11	32	14	22	17	16	1,5	2,5	32	0,18	0,33			
	G 1/2	G 1/2	8,2	32	8	22	17	16	0,9	1	32	0,17	0,23			
	G 1/2	G 1/2	8,2	32	10	22	17	16	0,9	1	32	0,17	0,23			
	G 1/2	G 1/2	10,2	32	12	22	17	16	0,9	1	32	0,17	0,24			
	G 1/2	G 1/2	8,2	32	10	19	15	14	0,75	0,75	27	0,11	0,18			
	G 1/2	G 1/2	8,5	32	10	19	15	16	0,75	0,75	32	0,23	0,29			

Model TW45-G

Technical drawing of Model TW45-G probe. The drawing shows a cross-section of the probe with various dimensions labeled. The dimensions are: E (Process connection), N (Length of male thread), G (Length of male thread for thermometer), D (Overall length), F1 (Connection to thermometer), K1 (Wall thickness), K2 (Tip thickness), S (Wall thickness), S1 (Tip thickness), SW (Flange), U1 (Insertion length), U2 (Bore size), D1 (Diameter of the sealing collar), and F1 (Thermowell external diameter).

Legend

E

K₁

N

L

K₂

S

S₁

SW

U₁

U₂

D₁

F₁

Material	Dimensions in mm													Weight in kg
	E	N	G	d ₁	D	F ₁	K ₁	K ₂	S	S ₁	SW	U ₁ x 73 mm	U ₂ x 410 mm	
Stainless steel 1.4571	G 1/2	G 1/2	7	26	12	14	12	2,5	3,5	27	0,14	0,34		
	G 1/2	G 1/2	9	26	14	14	12	2,5	3,5	27	0,14	0,37		
	G 1/2	G 1/2	11	26	14	14	12	1,5	2,5	27	0,12	0,30		
	G 1/2	G 1/2	8,2	26	10	14	12	0,9	1	27	0,13	0,20		
	G 1/2	G 1/2	10,2	26	12	14	12	0,9	1	27	0,13	0,20		
	G 1/2	G 1/2	7	32	12	16	14	2,5	3,5	32	0,22	0,43		
	G 1/2	G 1/2	9	32	14	16	14	2,5	3,5	32	0,22	0,46		
	G 1/2	G 1/2	11	32	14	16	14	1,5	2,5	32	0,20	0,38		
	G 1/2	G 1/2	8,2	32	8	16	14	0,9	1	32	0,21	0,28		
	G 1/2	G 1/2	8,2	32	10	16	14	0,9	1	32	0,21	0,28		
	G 1/2	G 1/2	10,2	32	12	16	14	0,9	1	32	0,20	0,27		