



JÍMKY TW45

Série TW45

TW45F-3244440

Jímka 12x10x0,9mm G1/2 G1/2 L=142mm

- Materiál nerez
- Připojení G



POPIS PRODUKTU

SPECIFIKACE

Insertion length 142 mm


Inside diameter 10 mm

Materiál Nerez ocel

Průměr 12 mm


Thickness 0,9 mm

Dimensions in mm



Material	Dimensions in mm											Weight in kg		
	E	N	G	d1	D	F1	H1	H2	K1	S	S1	SW	U1 ± 0.2 mm	U2 ± 0.2 mm
Stainless steel 1.4571	G1/2	G1/2	7	26	12	19	15	14	2.5	3.5	27	0.15	0.33	
	G1/2	G1/2	9	26	14	19	15	14	2.5	3.5	27	0.15	0.36	
	G1/2	G1/2	11	26	14	19	15	14	1.5	2.5	27	0.12	0.28	
	G1/2	G1/2	8	26	8	19	15	14	0.9	1	27	0.12	0.18	
	G1/2	G1/2	8.2	26	10	19	15	14	0.9	1	27	0.12	0.18	
	G1/2	G1/2	10.2	26	12	19	15	14	0.9	1	27	0.12	0.19	
	G1/2	G1/2	7	32	12	19	15	16	2.5	3.5	32	0.24	0.42	
	G1/2	G1/2	9	32	14	19	15	16	2.5	3.5	32	0.24	0.45	
	G1/2	G1/2	11	32	14	19	15	16	1.5	2.5	32	0.22	0.37	
	G1/2	G1/2	8.2	32	8	19	15	16	0.9	1	32	0.21	0.27	
	G1/2	G1/2	8.2	32	10	19	15	16	0.9	1	32	0.21	0.27	
	G1/2	G1/2	10.2	32	12	19	15	16	0.9	1	32	0.21	0.28	
	G1/2	G1/2	7	32	12	22	17	16	2.5	3.5	32	0.20	0.38	
	G1/2	G1/2	9	32	14	22	17	16	2.5	3.5	32	0.20	0.41	
	G1/2	G1/2	11	32	14	22	17	16	1.5	2.5	32	0.18	0.33	
	G1/2	G1/2	8.2	32	8	22	17	16	0.9	1	32	0.17	0.23	
Copper	G1/2	G1/2	8.2	32	10	22	17	16	0.9	1	32	0.17	0.23	
	G1/2	G1/2	10.2	32	12	22	17	16	0.9	1	32	0.17	0.24	
	G1/2	G1/2	8.5	26	10	19	15	14	0.75	0.75	27	0.11	0.18	
	G1/2	G1/2	8.5	32	10	22	17	16	0.75	0.75	32	0.23	0.29	

Model TW45-G



Material	Dimensions in mm										Weight in kg	
	E	N	G d1	D d1	F1	K1	K2	S	S1	SW	U1 ± 0.2 mm	U2 ± 0.2 mm
Stainless steel 1.4571	G1/2	G1/2	7	26	12	14	12	2.5	3.5	27	0.14	0.34
	G1/2	G1/2	9	26	14	14	12	2.5	3.5	27	0.14	0.37
	G1/2	G1/2	11	26	14	14	12	1.5	2.5	27	0.12	0.30
	G1/2	G1/2	8.2	26	10	14	12	0.9	1	27	0.13	0.20
	G1/2	G1/2	8.2	26	10	14	12	0.9	1	27	0.13	0.20
	G1/2	G1/2	10.2	26	12	14	12	0.9	0.9	27	0.11	0.18
	G1/2	G1/2	7	32	12	16	14	2.5	3.5	32	0.22	0.43
	G1/2	G1/2	9	32	14	16	14	2.5	3.5	32	0.22	0.46
	G1/2	G1/2	11	32	14	16	14	1.5	2.5	32	0.20	0.38
	G1/2	G1/2	8.2	32	8	16	14	0.9	1	32	0.21	0.28
	G1/2	G1/2	8.2	32	10	16	14	0.9	1	32	0.21	0.28
	G1/2	G1/2	10.2	32	12	16	14	0.9	1	32	0.21	0.27