

JIMKY TW45

Série TW45

TW45F-3244466

Jímka 12x10x0,9mm G1/2 G1/2 L=232mm




- Materiál nerez
- Připojení G

POPIS PRODUKTU

SPECIFIKACE


Insertion length	232 mm
Inside diameter	10 mm
Material	Nerez ocel
Průměr	12 mm
Thickness	0,9 mm

Dimensions in mm



Material	Dimensions in mm										Weight in g				
	E	G	G ₁	G ₂	D ₁	D ₂	F ₁	H ₁	H ₂	S	S ₁	SW	± 0.05 mm	± 0.02 mm	
Stainless steel 1.4571	G ₁ 0.8	G ₁ 0.7	7	26	12	18	15	14	2.5	3.5	27	0.15	0.33		
	G ₁ 0.8	G ₁ 0.7	9	26	12	18	15	14	2.5	3.5	27	0.15	0.33		
	G ₁ 0.8	G ₁ 0.7	11	26	14	18	15	14	2.5	3.5	27	0.12	0.28		
	G ₁ 0.8	G ₁ 0.7	12	26	14	18	15	14	2.5	3.5	27	0.12	0.28		
	G ₁ 0.8	G ₁ 0.7	14	26	14	18	15	14	2.5	3.5	27	0.12	0.28		
	G ₁ 0.8	G ₁ 0.7	16	26	14	18	15	14	2.5	3.5	27	0.12	0.28		
	G ₁ 0.8	G ₁ 0.7	18	26	14	18	15	14	2.5	3.5	27	0.12	0.28		
	G ₁ 0.8	G ₁ 0.7	20	26	14	18	15	14	2.5	3.5	27	0.12	0.28		
	G ₁ 0.8	G ₁ 0.7	22	26	14	18	15	14	2.5	3.5	27	0.12	0.28		
	G ₁ 0.8	G ₁ 0.7	24	26	14	18	15	14	2.5	3.5	27	0.12	0.28		
	G ₁ 0.8	G ₁ 0.7	26	26	14	18	15	14	2.5	3.5	27	0.12	0.28		
	G ₁ 0.8	G ₁ 0.7	28	26	14	18	15	14	2.5	3.5	27	0.12	0.28		
Stainless steel 1.4571	G ₁ 0.8	G ₁ 0.7	32	12	12	18	15	16	2.5	3.8	32	0.24	0.42		
	G ₁ 0.8	G ₁ 0.7	9	32	12	18	15	16	2.5	3.8	32	0.24	0.42		
	G ₁ 0.8	G ₁ 0.7	11	32	14	18	15	16	1.5	2.5	32	0.22	0.37		
	G ₁ 0.8	G ₁ 0.7	12	32	14	18	15	16	1.5	2.5	32	0.22	0.37		
	G ₁ 0.8	G ₁ 0.7	14	32	14	18	15	16	1.5	2.5	32	0.22	0.37		
	G ₁ 0.8	G ₁ 0.7	16	32	14	18	15	16	1.5	2.5	32	0.22	0.37		
	G ₁ 0.8	G ₁ 0.7	18	32	14	18	15	16	1.5	2.5	32	0.22	0.37		
	G ₁ 0.8	G ₁ 0.7	20	32	14	18	15	16	1.5	2.5	32	0.22	0.37		
	G ₁ 0.8	G ₁ 0.7	22	32	14	18	15	16	1.5	2.5	32	0.22	0.37		
	G ₁ 0.8	G ₁ 0.7	24	32	14	18	15	16	1.5	2.5	32	0.22	0.37		
	G ₁ 0.8	G ₁ 0.7	26	32	14	18	15	16	1.5	2.5	32	0.22	0.37		
	G ₁ 0.8	G ₁ 0.7	28	32	14	18	15	16	1.5	2.5	32	0.22	0.37		
Stainless steel 1.4571	G ₁ 0.8	G ₁ 0.7	32	12	12	22	17	16	2.5	3.8	32	0.20	0.38		
	G ₁ 0.8	G ₁ 0.7	9	32	12	22	17	16	2.5	3.8	32	0.20	0.38		
	G ₁ 0.8	G ₁ 0.7	11	32	14	22	17	16	1.5	2.5	32	0.18	0.33		
	G ₁ 0.8	G ₁ 0.7	12	32	14	22	17	16	1.5	2.5	32	0.18	0.33		
	G ₁ 0.8	G ₁ 0.7	14	32	14	22	17	16	1.5	2.5	32	0.18	0.33		
Stainless steel 1.4571	G ₁ 0.8	G ₁ 0.7	16	32	14	22	17	16	1.5	2.5	32	0.18	0.33		
	G ₁ 0.8	G ₁ 0.7	18	32	14	22	17	16	1.5	2.5	32	0.18	0.33		
	G ₁ 0.8	G ₁ 0.7	20	32	14	22	17	16	1.5	2.5	32	0.18	0.33		
	G ₁ 0.8	G ₁ 0.7	22	32	14	22	17	16	1.5	2.5	32	0.18	0.33		
	G ₁ 0.8	G ₁ 0.7	24	32	14	22	17	16	1.5	2.5	32	0.18	0.33		
Copper	G ₁ 0.8	G ₁ 0.7	32	12	12	18	15	14	2.5	3.5	27	0.11	0.18		
	G ₁ 0.8	G ₁ 0.7	9	32	12	18	15	14	2.5	3.5	27	0.11	0.18		
	G ₁ 0.8	G ₁ 0.7	11	32	14	18	15	14	2.5	3.5	27	0.11	0.18		
	G ₁ 0.8	G ₁ 0.7	12	32	14	18	15	14	2.5	3.5	27	0.11	0.18		
	G ₁ 0.8	G ₁ 0.7	14	32	14	18	15	14	2.5	3.5	27	0.11	0.18		

Model TW45-G



Material	Dimensions in mm										Weight in kg		
	ϕ	ϕ_1	ϕ_2	ϕ_3	ϕ_4	ϕ_5	ϕ_6	ϕ_7	ϕ_8	ϕ_9			
Stainless steel 1.4571	G 1/8	G 1/8	G 1/8	7	25	12	14	12	2.5	3.5	27	0.14	0.34
	G 1/8	G 1/8	G 1/8	9	26	14	14	12	2.5	3.5	27	0.14	0.37
	G 1/8	G 1/8	G 1/8	11	26	14	14	12	1.5	2.5	27	0.12	0.30
	G 1/8	G 1/8	G 1/8	6.2	26	12	12	12	0.9	1	27	0.13	0.20
	G 1/8	G 1/8	G 1/8	8.2	26	12	14	12	0.9	1	27	0.13	0.20
	G 1/8	G 1/8	G 1/8	10.2	26	12	14	12	0.9	1	27	0.13	0.21
	G 1/8	G 1/8	G 1/8	32	32	12	16	14	2.5	3.5	32	0.22	0.43
	G 1/8	G 1/8	G 1/8	9	32	14	16	14	2.5	3.5	32	0.22	0.46
	G 1/8	G 1/8	G 1/8	11	32	16	16	14	1.5	2.5	32	0.20	0.46
	G 1/8	G 1/8	G 1/8	6.2	32	8	16	14	0.9	1	32	0.21	0.29
G 1/8	G 1/8	G 1/8	8.2	32	10	16	14	0.9	1	32	0.21	0.28	
G 1/8	G 1/8	G 1/8	10.2	32	12	16	14	0.9	1	32	0.21	0.28	