



Poptávka

JÍMKY TW45

Série TW45

TW45F-3244458

Jímka 12x10x0,9mm G1/2 G1/2 L=182mm

- Materiál nerez
- Připojení G



POPIS PRODUKTU

SPECIFIKACE

Insertion length	182 mm
Inside diameter	10 mm
Materiál	Nerez ocel
Průměr	12 mm
Thickness	0,9 mm


Dimensions in mm

Model TW45-F

Legend:

- E Process connection
- N Length of female thread
- Ø d1 Length of male thread
- Ø D1 Overall length
- K1 Connection to thermometer
- K2 Tip thickness
- S Wall thickness
- S1 Flange
- SW Insertion length
- U1 Bore size
- Ø d2 Diameter of the sealing collar
- Ø F1 Thermowell external diameter

Material	Dimensions in mm	Weight in kg
	E N Ø d1 Ø D1 K1 K2 S S1 SW U1 Ø d2 Ø F1	U1 = 82 mm U1 = 182 mm
Stainless steel 1.4571	G 1/2 G 1/2 7 26 12 19 15 14 2,5 3,5 27 0,15 0,33	
G 1/2 G 1/2 9 26 14 19 15 14 2,5 3,5 27 0,15 0,36		
G 1/2 G 1/2 11 26 14 19 15 14 1,5 2,5 27 0,12 0,28		
G 1/2 G 1/2 8 26 8 19 15 14 0,9 1 27 0,12 0,18		
G 1/2 G 1/2 8,2 26 10 19 15 14 0,9 1 27 0,12 0,18		
G 1/2 G 1/2 10,2 26 12 19 15 14 0,9 1 27 0,12 0,19		
G 1/2 G 1/2 7 32 12 19 15 16 2,5 3,5 32 0,24 0,42		
G 1/2 G 1/2 9 32 14 19 15 16 2,5 3,5 32 0,24 0,45		
G 1/2 G 1/2 11 32 14 19 15 16 1,5 2,5 32 0,22 0,37		
G 1/2 G 1/2 8,2 32 8 19 15 16 0,9 1 32 0,21 0,27		
G 1/2 G 1/2 8,2 32 10 19 15 16 0,9 1 32 0,21 0,27		
G 1/2 G 1/2 10,2 32 12 19 15 16 0,9 1 32 0,21 0,28		
G 1/2 G 1/2 7 32 12 22 17 16 2,5 3,5 32 0,20 0,38		
G 1/2 G 1/2 9 32 14 22 17 16 2,5 3,5 32 0,20 0,41		
G 1/2 G 1/2 11 32 14 22 17 16 1,5 2,5 32 0,18 0,33		
G 1/2 G 1/2 8,2 32 8 22 17 16 0,9 1 32 0,17 0,23		
G 1/2 G 1/2 8,2 32 10 22 17 16 0,9 1 32 0,17 0,23		
G 1/2 G 1/2 10,2 32 12 22 17 16 0,9 1 32 0,17 0,24		
Copper	G 1/2 G 1/2 8,5 26 10 19 15 14 0,75 0,75 27 0,11 0,18	
G 1/2 G 1/2 8,5 26 10 19 15 16 0,75 0,75 32 0,23 0,29		

Model TW45-G 	Legend: - E Process connection - N Length of male thread - Ø d1 Length of male thread for thermometer - Ø D1 Overall length - K1 Connection to thermometer - K2 Tip thickness - S Wall thickness - S1 Flange - SW Insertion length - U1 Bore size - Ø d2 Diameter of the sealing collar - Ø F1 Thermowell external diameter <table> <tr> <th>Material</th><th colspan="12">Dimensions in mm</th><th>Weight in kg</th></tr> <tr> <th></th><th>E</th><th>N</th><th>Ø d1</th><th>Ø D1</th><th>K1</th><th>K2</th><th>S</th><th>S1</th><th>SW</th><th>U1</th><th>Ø d2</th><th>Ø F1</th><th>U1 = 73 mm</th><th>U1 = 410 mm</th></tr> <tr> <td>Stainless steel 1.4571</td><td>G 1/2</td><td>G 1/2</td><td>7</td><td>26</td><td>12</td><td>14</td><td>12</td><td>2,5</td><td>3,5</td><td>27</td><td>0,14</td><td>0,34</td><td></td><td></td></tr> <tr> <td></td><td>G 1/2</td><td>G 1/2</td><td>9</td><td>26</td><td>14</td><td>14</td><td>12</td><td>2,5</td><td>3,5</td><td>27</td><td>0,14</td><td>0,37</td><td></td><td></td></tr> <tr> <td></td><td>G 1/2</td><td>G 1/2</td><td>11</td><td>26</td><td>14</td><td>14</td><td>12</td><td>1,5</td><td>2,5</td><td>27</td><td>0,12</td><td>0,30</td><td></td><td></td></tr> <tr> <td></td><td>G 1/2</td><td>G 1/2</td><td>8,2</td><td>26</td><td>8</td><td>14</td><td>12</td><td>0,9</td><td>1</td><td>27</td><td>0,13</td><td>0,20</td><td></td><td></td></tr> <tr> <td></td><td>G 1/2</td><td>G 1/2</td><td>10,2</td><td>26</td><td>10</td><td>14</td><td>12</td><td>0,9</td><td>1</td><td>27</td><td>0,13</td><td>0,20</td><td></td><td></td></tr> <tr> <td></td><td>G 1/2</td><td>G 1/2</td><td>7</td><td>32</td><td>12</td><td>16</td><td>14</td><td>2,5</td><td>3,5</td><td>32</td><td>0,22</td><td>0,43</td><td></td><td></td></tr> <tr> <td></td><td>G 1/2</td><td>G 1/2</td><td>9</td><td>32</td><td>14</td><td>16</td><td>14</td><td>2,5</td><td>3,5</td><td>32</td><td>0,22</td><td>0,46</td><td></td><td></td></tr> <tr> <td></td><td>G 1/2</td><td>G 1/2</td><td>11</td><td>32</td><td>14</td><td>16</td><td>14</td><td>1,5</td><td>2,5</td><td>32</td><td>0,20</td><td>0,38</td><td></td><td></td></tr> <tr> <td></td><td>G 1/2</td><td>G 1/2</td><td>8,2</td><td>32</td><td>8</td><td>16</td><td>14</td><td>0,9</td><td>1</td><td>32</td><td>0,21</td><td>0,28</td><td></td><td></td></tr> <tr> <td></td><td>G 1/2</td><td>G 1/2</td><td>8,2</td><td>32</td><td>10</td><td>16</td><td>14</td><td>0,9</td><td>1</td><td>32</td><td>0,21</td><td>0,28</td><td></td><td></td></tr> <tr> <td></td><td>G 1/2</td><td>G 1/2</td><td>10,2</td><td>32</td><td>12</td><td>16</td><td>14</td><td>0,9</td><td>1</td><td>32</td><td>0,20</td><td>0,27</td><td></td><td></td></tr> </table>	Material	Dimensions in mm												Weight in kg		E	N	Ø d1	Ø D1	K1	K2	S	S1	SW	U1	Ø d2	Ø F1	U1 = 73 mm	U1 = 410 mm	Stainless steel 1.4571	G 1/2	G 1/2	7	26	12	14	12	2,5	3,5	27	0,14	0,34				G 1/2	G 1/2	9	26	14	14	12	2,5	3,5	27	0,14	0,37				G 1/2	G 1/2	11	26	14	14	12	1,5	2,5	27	0,12	0,30				G 1/2	G 1/2	8,2	26	8	14	12	0,9	1	27	0,13	0,20				G 1/2	G 1/2	10,2	26	10	14	12	0,9	1	27	0,13	0,20				G 1/2	G 1/2	7	32	12	16	14	2,5	3,5	32	0,22	0,43				G 1/2	G 1/2	9	32	14	16	14	2,5	3,5	32	0,22	0,46				G 1/2	G 1/2	11	32	14	16	14	1,5	2,5	32	0,20	0,38				G 1/2	G 1/2	8,2	32	8	16	14	0,9	1	32	0,21	0,28				G 1/2	G 1/2	8,2	32	10	16	14	0,9	1	32	0,21	0,28				G 1/2	G 1/2	10,2	32	12	16	14	0,9	1	32	0,20	0,27		
Material	Dimensions in mm												Weight in kg																																																																																																																																																																																						
	E	N	Ø d1	Ø D1	K1	K2	S	S1	SW	U1	Ø d2	Ø F1	U1 = 73 mm	U1 = 410 mm																																																																																																																																																																																					
Stainless steel 1.4571	G 1/2	G 1/2	7	26	12	14	12	2,5	3,5	27	0,14	0,34																																																																																																																																																																																							
	G 1/2	G 1/2	9	26	14	14	12	2,5	3,5	27	0,14	0,37																																																																																																																																																																																							
	G 1/2	G 1/2	11	26	14	14	12	1,5	2,5	27	0,12	0,30																																																																																																																																																																																							
	G 1/2	G 1/2	8,2	26	8	14	12	0,9	1	27	0,13	0,20																																																																																																																																																																																							
	G 1/2	G 1/2	10,2	26	10	14	12	0,9	1	27	0,13	0,20																																																																																																																																																																																							
	G 1/2	G 1/2	7	32	12	16	14	2,5	3,5	32	0,22	0,43																																																																																																																																																																																							
	G 1/2	G 1/2	9	32	14	16	14	2,5	3,5	32	0,22	0,46																																																																																																																																																																																							
	G 1/2	G 1/2	11	32	14	16	14	1,5	2,5	32	0,20	0,38																																																																																																																																																																																							
	G 1/2	G 1/2	8,2	32	8	16	14	0,9	1	32	0,21	0,28																																																																																																																																																																																							
	G 1/2	G 1/2	8,2	32	10	16	14	0,9	1	32	0,21	0,28																																																																																																																																																																																							
	G 1/2	G 1/2	10,2	32	12	16	14	0,9	1	32	0,20	0,27																																																																																																																																																																																							