



JÍMKY TW45

Série TW45

TW45F-3278230

Jímka 14x8x2,5mm G1/2 G1/2 L=142mm

- Materiál nerez
- Připojení G



POPIS PRODUKTU

SPECIFIKACE

Insertion length 142 mm

Inside diameter 8 mm

Materiál Nerez ocel

Průměr 14 mm

Thickness 2,5 mm

Dimensions in mm

Model TW45-F

Legend:

- E Process connection
- N Female thread for female thread
- Ø d1 Length of male thread
- N Length of male thread
- L Overall length
- K1 Connection to thermometer
- K2 Tip thickness
- S Wall thickness
- S1 Tip thickness
- SW Flange
- U1 Insertion length
- Ø d2 Bore size
- Ø F1 Diameter of the sealing collar
- Ø F2 Thermowell external diameter

Material	Dimensions in mm													Weight in kg	
	E	N	Ø d1	Ø D1	G 1/2	G 1/2	H1	H2	K1	B	S	S1	SW	U1 ± 0.2 mm	U1 ± 0.2 mm
Stainless steel 1.4571	G 1/2	G 1/2	7	26	12	18	15	14	2.5	3.5	27	0.15	0.33		
	G 1/2	G 1/2	9	26	14	19	15	14	2.5	3.5	27	0.15	0.36		
	G 1/2	G 1/2	11	26	14	19	15	14	1.5	2.5	27	0.12	0.28		
	G 1/2	G 1/2	8	26	8	19	15	14	0.9	1	27	0.12	0.18		
	G 1/2	G 1/2	8.2	26	10	19	15	14	0.9	1	27	0.12	0.18		
	G 1/2	G 1/2	10.2	26	12	19	15	14	0.9	1	27	0.12	0.19		
	G 1/2	G 1/2	7	32	12	19	15	16	2.5	3.5	32	0.24	0.42		
	G 1/2	G 1/2	9	32	14	19	15	16	2.5	3.5	32	0.24	0.45		
	G 1/2	G 1/2	11	32	14	19	15	16	1.5	2.5	32	0.22	0.37		
	G 1/2	G 1/2	8.2	32	8	19	15	16	0.9	1	32	0.21	0.27		
Copper	G 1/2	G 1/2	8.2	32	10	19	15	16	0.9	1	32	0.21	0.27		
	G 1/2	G 1/2	10.2	32	12	19	15	16	0.9	1	32	0.21	0.28		
	G 1/2	G 1/2	7	32	12	22	17	16	2.5	3.5	32	0.20	0.38		
	G 1/2	G 1/2	9	32	14	22	17	16	2.5	3.5	32	0.20	0.41		
	G 1/2	G 1/2	11	32	14	22	17	16	1.5	2.5	32	0.18	0.33		
	G 1/2	G 1/2	8.2	32	8	22	17	16	0.9	1	32	0.17	0.23		
	G 1/2	G 1/2	8.2	32	10	22	17	16	0.9	1	32	0.17	0.23		
	G 1/2	G 1/2	10.2	32	12	22	17	16	0.9	1	32	0.17	0.24		
	G 1/2	G 1/2	8.5	32	10	19	15	14	0.75	0.75	27	0.11	0.18		
	G 1/2	G 1/2	8.5	32	10	19	15	16	0.75	0.75	32	0.23	0.29		

Model TW45-G

Legend:

- E Process connection
- N Length of male thread
- Ø d1 Length of male thread for thermometer
- Ø D1 Overall length
- K1 Connection to thermometer
- K2 Tip thickness
- S Wall thickness
- S1 Tip thickness
- SW Flange
- U1 Insertion length
- Ø d2 Bore size
- Ø F1 Diameter of the sealing collar
- Ø F2 Thermowell external diameter

Material	Dimensions in mm	Weight in kg
	E N Ø d1 Ø D1 K1 K2 S S1 SW U1 Ø d2 Ø F1	U1 ± 0.2 mm U1 ± 0.2 mm
Stainless steel 1.4571	G 1/2 G 1/2 7 26 12 14 12 2.5 3.5 27 0.14 0.34	
G 1/2 G 1/2 9 26 14 14 12 2.5 3.5 27 0.14 0.37		
G 1/2 G 1/2 11 26 14 14 12 1.5 2.5 27 0.12 0.30		
G 1/2 G 1/2 8.2 26 10 14 12 0.9 1 27 0.13 0.20		
G 1/2 G 1/2 10.2 26 12 14 12 0.9 1 27 0.13 0.20		
G 1/2 G 1/2 7 32 12 16 14 2.5 3.5 32 0.22 0.43		
G 1/2 G 1/2 9 32 14 16 14 2.5 3.5 32 0.22 0.46		
G 1/2 G 1/2 11 32 14 16 14 1.5 2.5 32 0.20 0.38		
G 1/2 G 1/2 8.2 32 8 16 14 0.9 1 32 0.21 0.28		
G 1/2 G 1/2 8.2 32 10 16 14 0.9 1 32 0.21 0.28		
G 1/2 G 1/2 10.2 32 12 16 14 0.9 1 32 0.20 0.27		