



TERMOČLÁNKY TC47-MT

Série TC47-MT

TC47-MT
Termočlánek



- Teplota -40°C až 750°C
- K, J, K, T
- Tělo nerez



POPIS PRODUKTU

SPECIFIKACE

Provozní teplota max. 750 °C

Provozní teplota min. -40 °C

Manifold block ■ Stainless steel ■ Others on request		Lead wire covering ■ None ■ Stainless steel overbraid (no tracer) ■ Stainless steel overbraid (with tracer) ■ Tin copper overbraid ■ Interlocking flexible armour
Junction ■ Grounded (unisolated) ■ Ungrounded (isolated)		Termination at lead end ■ Bare ends ■ Standard thermo plug 2-pin (male) ■ Miniature thermo plug 2-pin (male)
Tip diameter (Ø) ■ 4 mm ■ Others on request		
Tip length ■ 12 mm ■ 20 mm ■ 25 mm ■ Others on request		
Lead length ■ 500 mm ■ 1000 mm ■ 1500 mm ■ 2000 mm ■ 2500 mm ■ Others on request		
Lead wire ■ Fibreglass / Fiberglass ■ PTFE / PTFE ■ PVC / PVC ■ Kapton / Kapton ■ Others on request		
		Calibration type ■ J ANSI MC96.1 red Ø white Ø ■ F ANSI MC96.1 red Ø yellow Ø ■ T ANSI MC96.1 red Ø blue Ø ■ J IEC 584-3 white Ø black Ø ■ K IEC 584-3 white Ø green Ø ■ T IEC 584-3 white Ø brown Ø ■ J DIN 43714 blue Ø red Ø ■ K DIN 43714 green Ø red Ø ■ T DIN 43714 brown Ø red Ø ■ Others on request