



TERMOČLÁNKY TC47-NT

Série TC47-NT

TC47-NT
Termočlánek

- Teplota -40°C až 750°C
- K, J, K, T
- Tělo nerez



POPIS PRODUKTU

SPECIFIKACE

Provozní teplota max. 750 °C

Provozní teplota min. -40 °C



Nozzle bolt material

- Stainless steel
- Brass
- Others on request

Junction

- Grounded (isolated)
- Ungrounded (isolated)

Nozzle bolt thread size

- 1/4 x 28
- M5
- M8
- Others on request

Lead length

- 500 mm
- 1000 mm
- 1500 mm
- 2000 mm
- 2500 mm
- Others on request

Lead wire

- Fibreglass / Fibreglass
- PTFE / PTFE
- PVC / PVC
- Kapton / Kapton
- Others on request

Lead wire covering

- None
- Stainless steel overbraid (no tracer)
- Stainless steel overbraid (with tracer)
- Tin copper overbraid

Termination at lead end

- Bare ends

- Standard thermo plug 2-pin (male)
- Miniature thermo plug 2-pin (male)

- Standard plug with cable clamp (male)
- Miniature plug with cable clamp (male)

- Lemosa plug size 1G (male)
- Lemosa plug size 2S (male)

- Screw-in plug, Binder (male)

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request

- Others on request