



TERMOČLÁNKY TC47-AC

Série TC47-AC



TC47-AC
Termočlánek

- Teplota -40°C až 750°C
- K, J, K, T
- Tělo nerez



POPIS PRODUKTU

SPECIFIKACE

Provozní teplota max.	750 °C
Provozní teplota min.	-40 °C

Adjustable compression version ■ Straight ■ 45° bend ■ 90° bend	Lead wire ■ Fibreglass / fibreglass ■ PTFE / PTFE ■ PVC / PVC ■ Kapton / Kapton ■ Others on request
Junction ■ Grounded (unisolated) ■ Ungrounded (isolated)	Lead wire covering ■ None ■ Stainless steel overbraid (no tracer) ■ Stainless steel overbraid (with tracer) ■ Tin copper overbraid ■ Interlocking flexible armour
Probe diameter ■ 3/16" ■ 1/4" ■ 3/8" ■ 4 mm ■ 6 mm ■ 8 mm ■ Others on request	Termination at lead end ■ Bare ends ■ Standard thermo plug 2-pin (male) ■ Miniature thermo plug 2-pin (male) ■ Standard plug with cable clamp (male) ■ Miniature plug with cable clamp (male) ■ Lemosa plug size 15 (male) ■ Lemosa plug size 25 (male) ■ Screw-in plug, Binder (male) ■ Others on request
Probe length ■ Standard: 100 mm (4") ■ Others on request	Calibration type ■ J: ANSI MC96.1 red Ø white Ø ■ K: ANSI MC96.1 red Ø yellow Ø ■ T: ANSI MC96.1 red Ø blue Ø ■ J: IEC 584-3 white Ø black Ø ■ K: IEC 584-3 white Ø green Ø ■ T: IEC 584-3 white Ø brown Ø ■ J: DIN 43714 blue Ø red Ø ■ K: DIN 43714 green Ø red Ø ■ T: DIN 43714 brown Ø red Ø ■ Others on request
Compression fitting material ■ Brass ■ Stainless steel ■ None	
Thread size ■ Thread size on request	
Lead length ■ 500 mm ■ 1000 mm ■ 1500 mm ■ 2000 mm ■ 2500 mm ■ Others on request	